


LA TOLLERANZA PER I FUORI SQUADRO SI MISURA POGGIANDO UNA SQUADRA RETTIFICATA A 90° SU OGNI LATO DEL FILTRO E DETERMINANDO LO SCOSTAMENTO NELL' ANGOLO OPPOSTO DELLO STESSO LATO. LIMITE MAX 1mm

THE TOLLERANCE HAS TO BE MEASURED PLACING A GROUND TRIANGLE ON EVERY FILTER'S EDGE AND MEASURING THE DEVIATION AT THE OPPOSITE CORNER ON THE SAME EDGE. MAXIMUM LIMIT 1 mm



TOLERANCE CLASSES ISO 2768-1	GENERAL TOLERANCE LINEAR DIMENSION						
	0.5-3	3-6	6-30	30-120	120-400	400-1000	1000-2000
FINE	±0.05	±0.05	±0.1	±0.15	±0.2	±0.3	±0.5
MEDIUM	±0.1	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2
COARSE	±0.2	±0.3	±0.5	±0.8	±1.2	±2	±3
VERY COARSE	-	-	±0.5	±1	±1.5	±4	±6

These drawings and specifications are the property of Franke Technology and Trademark Ltd and shall not be reproduced, copied or transferred to any third party without the prior written permission of Franke Technology and Trademark Ltd, Switzerland. It is strictly prohibited to get quotes from the drawing or bring modifications whatsoever without the prior written consent of Franke Technology and Trademark Ltd.

Created by Solutions

Creation date 03-Aug-2011 11:12

Modif.by Solutions

Doc.Type PART

Approved by Palazzi, Walter

Approval date 25-Sep-2020

Doc. status Released

Drawing N. FIF_008

Rev 02

Modification description
CRO00000060941-Revisione maniglie disegni FIF e FIG

Denomination
CASSETTE FILTER 253 X 300

Material
AISI 430

Thickness

Weight
Kg

Lang EN

Scale 1:2

Form A3

Sheet 1/1

FRANKE

FABER

©Copyright Franke Technology and Trademark Ltd